# **OFFICE OF THE PTA**

## GEC Palakkad, Sreekrishnapuram, 678 633

### **Notice Inviting Quotation**

Sealed Quotations are invited for CCTV Monitoring System. The Quotation may be submitted to President PTA, GEC Palakkad, Sreekrishnapuram,678 633 up to 5.00 PM on 27.04.2022. The envelope should be superscripted in boldletters with "QUOTATION FOR CCTV MONITORING SYSTEM ".The opening of quotation shall be done at 2.00 pm on 28.04.2022.

Work name: Installation of CCTV camera

General Terms & Conditions:

1. The quotations received after deadline & unsealed shall not be entertained under anycircumstances whatsoever.

2.Quotations must be in the letter head of the firm duly signed by theProprietor/Partner/Director or their authorized representative. In case of signing of quotationby the authorized representative letter of authorization must be attached with the quotation.

3.Rates must be quoted in Indian rupees and as per the format specified taxes extra if anymust be writtenseparately.

4.No overwriting or cutting is permitted in the rate. If found, the quotation shall be summarilyrejected.

5. The firm/agency may satisfy the following conditions and attach self-attested copy of thesame with the quotation:

-The firm shall have valid GST number

-The firm should not be black listed by any Govt. Agency/Dept.

6. Any conditional quotation shall be rejected summarily.

7. Interested firm must visit the site, if needed for survey, before submitting the quotation.

8. The quantity of items given in the Quotation is tentative, which may be increased ordecreased as per actualrequirement of this office.

9. Work involves provision as well as installation of CCTV.

Contact Person: Prof. Balu John, HoD of Computer Science (9895 259 420)

Encl: Annexure 1(specification)

#### Proposal for Installing the CCTV Surveillance system at College Campus

#### Scope of the Work

Supply and installation of CCTV Surveillance system using indoor and outdoor Bullet cameras. The NVR is to be installed at Institution Data Centre. Installation of IP camera, NVR and networking up to the distribution switch is comes under the scope of the project. Existing fiber backbone can be used for the integration of the system.

#### **Proposed Locations**

As suggested by the PTA / Higher officials proposed locations are the Main Gates, Porch, Lobby, Principal office corridor and some of the other corridors.

#### Proposed Solution.

The proposed solution consists of 16 Channel NVR with minimum 30 days recording, 2 Nos of outdoor verifocal cameras and 6 nos indoor bullet cameras.

#### BOM

SI.	Item Description	Qty
1	4 MP Outdoor Verifocal 30M IR/Vandal-proof/HD/PoE	2
2	4 MP Indoor Bullet Camera 30M IR/Vandal-proof/HD/PoE	6
3	16 Channel NVR with 4 HDD Bay	1
4	6TB CCTV Hard disk	2
5	Cabling Using 25mm conduit (Mtrs)	400
6	Supply and Laying of CAT6 Cable	1000
8	40" Display	1
9	Core i5/8GB Console system	1
10	Installation and Fixing Charges	Lump- sum

#### General instructions

• All the equipments (Camera, NVR, [Display]) should be the same make

- The product should be in the market for last 3 years and show positive growth
- Network components should be compatible with our CISCO based network and the company should work in co-operation with our network team.
- Bidder must have completed minimum 3 CCTV projects
- OEM should be ISO 9001:2015, ISO 14001:2015 for manufacturing
- OEM of the camera should not be banned in India or anywhere globally for security reasons
- OEM shall have service centre in Kerala, with sufficient numbers of technical staff

#### **Detailed Specifications**

4 MP Bullet Camera		
Parameter	Values	
Туре	4 MP Bullet IP Camera IP66 Metal Body	
Sensor	1/2.7" Progressive scan CMOS Sensor0.01lux (Color), 0lux (IR on) , Auto/Manual, 1/3~1/10000s	
Lens	3.6 mm, M12	
Angle of view	FOV:85 °or More	
IR Range	30 Mtrs Smart IR, cut filter with auto switch	
Max Resolution	2560×1440	
Video Compression	H.265+, H.265,H.264+ , H.264	
Frame Rate	Min 25fps	
Image Settings	Configurable HLC , BLC , dWDR , Rol , AGC , Smart Defog	
Corridor Mode	Should be supported	
Motion Detection	Should be supported	
Smart Functions	Area Intrusion, Line Crossing	

Protocol	TCP/IP,ICMP, HTTP,HTTPS,DHCP,DNS,DDNS, RTP,RSTP,RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P, Bon- jour,IPV6,IPV4,DynDNS ,NO-IP DDNS, OrayDDNS, CN99DDNS, P2P
Compatibility	ONVF, CGI
Security	User authentication, IP address filtering, Video Mask
Connectivity	RJ45 10/100 Ethernet , P2P Direct Access
Power	PoE (IEEE 802.3af), 12V DC
Warranty	5 Years From OEM

4 MP Verifocal Outdoor Camera				
Parameter	Values			
Туре	4 MP IP Camera IP66 Metal Body			
Sensor	1/2.7" Progressive scan CMOS Sensor0.01lux (Color), 0lux (IR on) , Auto/Manual, 1/3~1/10000s			
Lens	3.6 mm, M12			
Angle of view	FOV:85 °or More			
IR Range	30 Mtrs Smart IR, cut filter with auto switch			
Max Resolution	2560×1440			
Video	H.265+, H.265,H.264+ , H.264			
Compression				
Frame Rate	Min 25fps			
Image Settings	Configurable HLC , BLC , dWDR , Rol , AGC , Smart Defog			
Corridor Mode	Should be supported			
Motion Detection	Should be supported			

Smart Functions	Area Intrusion, Line Crossing
Protocol	TCP/IP,ICMP,HTTP,HTTPS,DHCP,DNS,DDNS, RTP,RSTP,RTCP,NTP,IGMP,UPnP,SMTP,UPnP-TM,P2P, Bon- jour,IPV6,IPV4,DynDNS ,NO-IP DDNS, OrayDDNS, CN99DDNS, P2P
Compatibility	ONVF, CGI
Security	User authentication, IP address filtering, Video Mask
Connectivity	RJ45 10/100 Ethernet , P2P Direct Access
Power	PoE (IEEE 802.3af), 12V DC
Warranty	5 Years From OEM

16 Channel NVR		
Parameter	Values	
Туре	16 Channel NVR	
Storegae	Upto 4 SATA HDD with Raid 0,1,5,10 Support	
HDD	1 TB - 10 TB Enterprise HDD	
Connectivity	2 x 10/100/1000 NIC	
Outpur	1 VGA, 1 HDMI,	
Record Resolution	Real time Recording 5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	
Play back Resolution	Real time Play back 5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	
Video Compression	H.265, H.264 and MPEG	
Protocol	IPv4, TCP, UDP, P2P, UPnP, NTP, DHCP, PPPoE	
Compatibility	ONVF, API	

Other Features	Intrusion detection, Cross line detection, Audio detection, Defocus de- tection, Scene change detection
Alarms	Channel loss
Warranty	5 Years (Minimum 3 years OEM)

Commercial Display		
Parameter	Values	
Туре	40" + Commercial IPS Display	
Input	HDMI, VGA	
USB	USB-C	
Warranty	5 Years (Minimum 3 years OEM)	